

新一代智能型自动变速箱清洗换油机

Automatic Transmission Oil Exchanger

ATF-9800

功能特点

- ※ 液晶触摸屏显示。智能车型数据库指引换油系统；
- ※ 功能菜单彩色图形显示。预留有可选功能(打印)；
- ※ 自带车型油量数据库；
- ※ 自动识别变速箱与散热器管路间的油流方向。无须区分进回油管；
- ※ 自动识别电源正、负极；
- ※ 变速箱油加注功能；
- ※ 自动变速箱清洗功能和变速箱新旧油自动更换功能；
- ※ 变速箱散热器油压与设备出油油压直观显示；
- ※ 智能电子控制新、旧油全自动等量交换；
- ※ 随意设定新旧油交换量；
- ※ 电子秤一键归零；
- ※ 多种专用接头，适用欧洲、美洲、亚洲各国车型；

技术参数

电压：DC12V
 最大功率：150W
 压力表：0~150psi
 出油管：2.3m
 回油管：2.3m
 排油管：1.5m
 油箱：20L×2
 重量：74 Kg
 包装尺寸：69×59×114cm

Features

- ※ Fully automatic operation. LCD touch screen display, color observation window design.
- ※ Optional functions
- ※ Own vehicle models program oil mass database
- ※ Intelligent vehicle model database system guide oil change system.
- ※ Automatic identification and intelligent switch the in/ out oil flow direction.
- ※ Automatic identification of power supply positive and negative.
- ※ Filling of automatic transmission oil.
- ※ Automatic circulating cleaning and changing of new/used oil for AT.
- ※ Visual displays the AT oil pressure and the oil outlet pressure of the unit.
- ※ Intelligent electronic control the full automatic equivalent change of new/used oil.
- ※ Randomly set new and used oil volume.
- ※ A key to zero of electronic weight.
- ※ Various special adapters are applicable to vehicle types made in Europe, America and Asia.

28家汽车制造商指定使用设备

出口 50 多个国家与地区

品质全球信赖



Specifications

Power supply: DC 12V
 Maximum power: 150W
 Pressure gauge: 0~150psi
 Fluid outlet hose: 2.3 m
 Fluid return hose: 2.3 m
 Fluid draining hose: 1.5 m
 Filter precision: 5 μm
 New/used fluid tank: 20L × 2
 Weight: 74Kg
 Size: 69 × 59 × 114cm



ATF随机配套接头

新一代智能型自动变速箱清洗换油机

Automatic Transmission Oil Exchanger

ATF-9800L

功能特点

- ※ 自动识别变速箱与散热器管路间的油流方向。无须区分进回油管；
- ※ 液晶屏显示,智能人性化操作,方便实用；
- ※ 变速箱油加注功能；
- ※ 自动识别电源正,负极；
- ※ 自动变速箱循环清洗功能和变速箱新旧油自动更换功能；
- ※ 变速箱散热器油压与设备出油油压直观显示；
- ※ 智能电子控制新、旧油全自动等量交换；
- ※ 随意设定新旧油交换量；
- ※ 电子秤一键归零；
- ※ 多种专用接头，适用欧洲、美洲、亚洲各国车型；

技术参数

电压：DC12V
 最大功率：150W
 压力表：0~150psi
 出油管：2.3m
 回油管：2.3m
 排油管：1.5m
 油箱：20L×2
 重量：74 Kg
 包装尺寸：69×59×114cm

Features

- ※ Fully automatic operation. Big LCD screen display.
- ※ Automatic identification and intelligent switch the in/out fluid flow direction.
- ※ Automatic identification of power supply positive and negative.
- ※ Filling of automatic transmission fluid.
- ※ Automatic circulating cleaning and exchanging of new/used fluid for automatic transmission.
- ※ Visual displays the fluid pressure of automatic radiator and the fluid outlet pressure of the unit.
- ※ Intelligent electronic control the full automatic equivalent exchange of new and used fluid.
- ※ Randomly set new and used oil volume.
- ※ A key to zero of electronic weight.
- ※ Various special adapters are applicable to vehicle types made in Europe, America and Asia.

28家汽车制造商指定使用设备

出口 50 多个国家与地区

品质全球信赖



Specifications

Power supply: DC 12V
 Maximum power: 150W
 Pressure gauge: 0~150psi
 Fluid outlet hose: 2.3 m
 Fluid return hose: 2.3 m
 Fluid draining hose: 1.5 m
 Filter precision: 5µm
 New/used fluid tank: 20L×2
 Weight: 74Kg
 Size: 69×59×114cm



ATF随机配套接头

自动变速箱深度养护专家

Automatic transmission fluid exchanger

ATF-9800E

功能特点

- ※ ARM CORTEX-A9 4核 1.6GHz, 1GB运行内存, 8GB存储空间, 工业显示屏 1024x600dpi, 400流明高亮度, 安卓智能系统, 多媒体处理, 用户交互界面, 高分辨率广角显示, 触摸滑动转换;
- ※ 除显示功能之外自带WIFI, 蓝牙、千兆以太网、USB、串口、便于数据采集传输、远程升级;
- ※ 除本地升级之外通过网络方式在线更新迭代应用程序, 无线链接油品信息;
- ※ 可加载广告宣传视频;
- ※ 可链接内窥镜, 打印机设备;
- ※ 对每次保养内容进行网络保存及通过车架号查询保养记录;
- ※ 功能菜单彩色图形显示, 可选打印功能;
- ※ 自带车型油量数据库;
- ※ 自动识别变速箱与散热器管路间油流方向, 无须区分进回油管;
- ※ 自动识别电源输入 (DC12v, AC220v) 可任意连接 DC12V/AC220V;
- ※ 自动变速箱油加注功能;
- ※ 自动变速箱清洗功能和变速箱新旧油自动更换功能;
- ※ 变速箱散热器油压与设备出油油压直观显示;
- ※ 智能电子控制新、旧油全自动等量交换;
- ※ 随意设定新旧油交换量;
- ※ 电子秤一键归零;
- ※ 多种专用接头, 适用欧洲、美洲、亚洲各国车型(可选购);

Features

- ※ ARM cortex-A9 4 core 1.6GHz, 1GB running memory, 8GB storage space, industrial display 1024x600dpi with 400 lumen high brightness. Android intelligent operating system, multimedia processing, gorgeous user interfaces, high resolution with wide angle display effect, touch and scroll switching.
- ※ Abundant hardware interfaces. In addition to the functional display, it has WIFI, bluetooth, Ethernet, USB, serial port to facilitate data acquisition and transmission
- ※ In addition to local upgrades, it can also update iterate applications online through internet, making maintenance more easier.
- ※ Large hardware expansion capacity that can link to endoscopes, printers, and more
- ※ Saving the maintenance data on the network and inquiring the maintenance records through the car frame number
- ※ Main menu with colored graphic icons. Optional functions are available (Printing/Heating).
- ※ Build-in database of vehicle models and fluid capacities
- ※ Automatic ID of power supply (DC12v and Ac220v).
- ※ Automatically identify fluid flow directions between transmission and radiator. No more need to distinguish in/out fluid tubes.
- ※ Automatically recognize power supply(DC12v, AC220v)
- ※ Function of refilling transmission fluid
- ※ Automatic cleaning transmission gearbox and automatic changing new and used transmission fluid.
- ※ Visual displays of the fluid pressure of transmission radiator and discharge pressure of the fluid out of equipment.
- ※ Intelligent electronic control of used and new fluid to perform equivalent exchange automatically
- ※ New and used fluid exchange capacity can be set freely.
- ※ Electronic scale with high accuracy and the function of one key to return to zero
- ※ Various of special adapters to fit the European, American and Asian cars.

29家汽车制造商指定使用设备

出口 50 多个国家与地区

品质全球信赖



技术参数

电压: DC12V/AC220V
 最大功率: 150W
 压力表: 0~150psi
 出油管: 2.5m
 回油管: 2.5m
 排油管: 1.5m
 油箱: 20L x 2
 重量: 74 Kg
 包装尺寸: 69 x 59 x 113cm

Specifications

Power supply: DC 12V/AC220V
 Maximum power: 150W
 Pressure gauge: 0~150psi
 Fluid outlet hose: 2.5 m
 Fluid return hose: 2.5 m
 Fluid draining hose: 1.5 m
 New/used fluid tank: 20L x 2
 Weight: 74Kg
 Size: 69 x 59 x 113cm



ATF随机配套接头

新一代智能型自动变速箱清洗换油机

Automatic Transmission Oil Exchanger



ATF-9900

功能特点

- ※ ARM CORTEX-A9 4核 1.6GHz, 1GB运行内存, 8GB存储空间, 工业显示屏 1024x600dpi, 400流明高亮度, 安卓智能系统, 多媒体处理, 用户交互界面, 高分辨率广角显示, 触摸滑动转换;
- ※ 除显示功能之外自带WIFI, 蓝牙、百兆以太网、USB、串口、便于数据采集传输、远程升级;
- ※ 除本地升级之外通过网络方式在线更新迭代应用程序, 无线链接油品信息;
- ※ 可加载广告宣传视频;
- ※ 可链接内窥镜, 打印机设备;
- ※ 对每次保养内容进行网络保存及通过车架号查询保养记录;
- ※ 功能菜单彩色图形显示, 可选打印功能;
- ※ 自带车型油量数据库;
- ※ 自动识别变速箱与散热器管路间油流方向, 无须区分进回油管;
- ※ 自动识别电源输入 (DC12v);
- ※ 自动变速箱油加注功能;
- ※ 自动变速箱清洗功能和变速箱新旧油自动更换功能;
- ※ 变速箱散热器油压与设备出油油压直观显示;
- ※ 智能电子控制新、旧油全自动等量交换;
- ※ 随意设定新旧油交换量;
- ※ 电子秤一键归零;
- ※ 多种专用接头, 适用欧洲、美洲、亚洲各国车型(可选购);

Features

- ※ ARM cortex-A9 4 core 1.6GHz, 1GB running memory, 8GB storage space, industrial display 1024x600dpi with 400 lumen high brightness. Android intelligent operating system, multimedia processing, gorgeous user interfaces, high resolution with wide angle display effect, touch and scroll switching.
- ※ Abundant hardware interfaces. In addition to the functional display, it has WIFI, bluetooth, Ethernet, USB, serial port to facilitate data acquisition and transmission
- ※ In addition to local upgrades, it can also update iterate applications online through internet, making maintenance more easier.
- ※ Large hardware expansion capacity that can link to endoscopes, printers, and more
- ※ Saving the maintenance data on the network and inquiring the maintenance records through the car frame number
- ※ Main menu with colored graphic icons. Optional functions are available (Printing/Heating).
- ※ Build-in database of vehicle models and fluid capacities
- ※ Automatic ID of power supply (DC12v)
- ※ Automatically identify fluid flow directions between transmission and radiator. No more need to distinguish in/out fluid tubes.
- ※ Automatically recognize power supply(DC12v)
- ※ Function of refilling transmission fluid
- ※ Automatic cleaning transmission gearbox and automatic changing new and used transmission fluid.
- ※ Visual displays of the fluid pressure of transmission radiator and discharge pressure of the fluid out of equipment.
- ※ Intelligent electronic control of used and new fluid to perform equivalent exchange automatically
- ※ New and used fluid exchange capacity can be set freely.
- ※ Electronic scale with high accuracy and the function of one key to return to zero
- ※ Various of special adapters to fit the European, American and Asian cars

28家汽车制造商指定使用设备

出口 50 多个国家与地区

品质全球信赖



技术参数

电压: DC12V
最大功率: 150W
压力表: 0~150psi
出油管: 2.3m
回油管: 2.3m
排油管: 1.5m
油箱: 20L x 2
重量: 65Kg
包装尺寸: 69 x 59 x 114cm

Specifications

Power supply: DC 12V
Maximum power: 150W
Pressure gauge: 0~150psi
Fluid outlet hose: 2.3m
Fluid return hose: 2.3 m
Fluid draining hose: 1.5 m
Filter precision: 5µm
New/used fluid tank: 20L x 2
Weight: 65Kg
Size: 69 x 59 x 114cm



ATF随机配套接头

汽车刹车油更换机

Engine Brake Oil Changemachine



BFE-9800E

功能特点

- ※ 带安卓智能操作系统，强大的多媒体处理能力，绚丽的用户交互界面，高分辨率广角显示效果，触摸滑动转换，操作简单，方便客户使用；
- ※ 丰富的硬件接口；除显示功能之外，自带WIFI, 蓝牙，以太网，USB，串口，便于数据采集传输；
- ※ 便捷的应用程序部署，除了本地升级之外，还可以通过网络的方式在线更新迭代应用程序，维护更为简单；
- ※ 强大的硬件扩展能力，可以链接内窥镜，打印机等设备；
- ※ 外观采用现代工业造型设计，结构紧凑、布局合理，色彩搭配丰富；
- ※ 产品具有网络保存和查询功能，可对每次保养内容进行网络保存及通过车架号查询保养记录；
- ※ 汽车刹车油更换机采用正压压入新油、负压吸出旧油的原理，提高换油速度和质量。配备各种车型的专用刹车油壶盖，与汽车刹车油油壶口相连。由换油机将具有一定压力的新刹车油经专用油壶盖注入刹车系统。旧刹车油由汽车刹车分泵排气口吸入所配专用废油收集罐中。直至各个分泵逐个排出新油为止；
- ※ 12V或220V电输入自动识别；

Features

- ※ Android intelligent operating system with powerful multimedia processing ability, gorgeous user interfaces, high resolution with wide angle display effect, touch and scroll switching. Simple and easy to use
- ※ Abundant hardware interfaces. In addition to the functional display, it has WIFI, bluetooth, Ethernet, USB, serial port to facilitate data acquisition and transmission
- ※ Convenient application deployment. In addition to local upgrades, it can also update iterate applications online through internet, making maintenance more easier.
- ※ Large hardware expansion capacity that can link to endoscopes, printers, and more.
- ※ The appearance adopts the modern industrial modeling with compact design, reasonable layout and rich color collocation.
- ※ With the functions of network storage and inquiry, saving the maintenance data on the network and inquiring the maintenance records through the car frame number
- ※ Use the principle of positive pressure pressing new fluid and negative pressure sucking used fluid. Brake fluid exchanger improves the exchange speed and quality. Equipped with various of brake fluid reservoir pot lids to suit different car models. The new brake fluid with certain pressure is injected into the brake system through the special fluid pot lids. The used brake fluid is sucked into a special waste fluid collection tank by the brake cylinders exhaust port until each cylinder discharges new fluid.
- ※ Automatic identification of 12V or 220V power input

技术参数

动力源：DC12V-200W
 工作压力：$2\text{kg}/\text{cm}^2$
 新油桶：10L
 旧油桶：10L
 重量：70 Kg
 包装尺寸：69×59×103cm

Specifications

Power supply: DC12V-200w
 Pressure gauge: $2\text{kg}/\text{cm}^2$
 New/used fluid tank: 10L x 2
 Weight: 70Kg
 Size: 69×59×103cm



安卓智能操作系统，高分辨率广角显示，自带WIFI、蓝牙、以太网、USB、网络在线更新迭代应用程序、可以链接内窥镜、打印机、网络保存和查询功能。
 Android Intelligent operating system with high-resolution wide-angle display, WIFI, Bluetooth, Ethernet, USB and network online update iterative applications. It may apply to link endoscopes, printers, saving and query function through internet.



随机配套接头

汽车刹车油换油机

Brake Oil Exchanger



BFE-6800

功能特点

- ※ 汽车刹车油更换机采用正压压入新油、付压吸出旧油的原理，提高换油速度和质量；
- ※ 配备各种车型的专用刹车油壶盖，与汽车刹车油壶口相连；
- ※ 由换油机将具有一定压力的新刹车油经专用油壶盖注入刹车系统；
- ※ 旧刹车油由汽车刹车分泵排气口吸入所配专用废油收集罐中。直至各个分泵逐个排出新油为止；
- ※ 四轮同步更换；

技术参数

动力源:压缩空气
工作压力: 2kg/cm^2
新油桶: 2.5L
旧油桶: 2.5L
重量: 30kg
包装尺寸: 61 x 53 x 100 cm

Features

- ※ Use the atmospheric pressure theory to infuse new fluid into the pot in positive pressure and suck old fluid from the pot in negative pressure, providing better quality and more efficient.
- ※ With various brake fluid reservoir pot lids to suit different car models
- ※ New brake fluid with certain pressure will be infused into the brake system through the special reservoir pot lid.
- ※ Old brake fluid is sucked into a special waste fluid collection tank by the brake cylinders exhaust port until each cylinder discharges new fluid.
- ※ Change four wheels at the same time

Specifications

Power source: Compressed air
Working pressure: 2kg/cm^2
New oil tank: 2.5L
Used oil tank: 2.5L
Weight: 30kg
Packing size: 61 x 53 x 100 cm

28家汽车制造商指定使用设备

出口 50 多个国家与地区

品质全球信赖



随机配套接头

多功能空调系统清洗机

Multifunction A/c Flush Machine



ACS-6800L

功能特点

- ※ 汽车空调蒸发箱可视化清洗机采用程控液晶屏按键设计，调整和设定简单、直观、方便；
- ※ 对蒸发箱清洗、杀菌、净化为一体；
- ※ 可以向风道内喷杀菌、净化和除味剂；也可以清洗空调冷凝器；
- ※ 去污剂和杀菌剂两个储液罐独立控制。可根据各种不同保养方式组合需要加入相应的液体；
- ※ 汽车蒸发箱等部位可视化手持内窥镜时实高清查看；
- ※ LED照明辅助；
- ※ 清洗管采用可调变形的蛇形管，操作灵活；
- ※ 汽车室内利用气雾和臭氧双重清洁消毒快速杀菌消除异味；
- ※ 臭氧杀菌去味；超微气雾负离子中和有害气体去味醒脑；

技术参数

输入电源电压：220V / 3A/150W
输入气源压力：8 kg/cm²
输出气源压力：0-5kg/cm²
雾化管：φ40x2m
3.5寸液晶显示屏
压力表：0~10kg/cm²
液体输出管：2.3m
去污剂/杀菌剂贮液瓶：600ML
重量：30kg
包装尺寸：61X53X100cm

Features

- ※ Automobile air conditioning evaporator cleaning machine is designed with programmable LCD screen, simple to set and easy to use.
- ※ Combined the multiple functions of cleaning, sterilization and purification of the evaporator in one.
- ※ Sterilization, purification and deodorization of the air duct, and washing air conditioning condenser as well.
- ※ Both liquid tanks of detergent and sterilant can be controlled independently. The corresponding liquid can be added as needed.
- ※ Evaporator and other parts can be viewed clearly at the visual endoscope.
- ※ Additional LED lighting
- ※ Cleaning hose is flexible and adjustable serpentine tube, easy to operate.
- ※ Use air mist spray and ozone to sterilize the air and eliminate odor in car's interior.
- ※ Ozone sterilizes air and ultra micro negative ion neutralizes harmful gas.

28家汽车制造商指定使用设备

出口 50 多个国家与地区

品质全球信赖



Specifications

Input power:220V / 3A/150W
Input air pressure:8 kg/cm²
Output air pressure:0-5kg/cm²
Spray hose:φ40x2m
3.5 inches LCD display
Pressure gauge:0~10kg/cm²
Output liquid hose:2.3m
Detergent/ Sterilant tank:600ML
Weight:30kg
Size:61X53X100cm



多功能空调系统清洗机

Multifunction A/c Flush Machine



ACS-9800

功能特点

- ※ 汽车空调蒸发箱可视化清洗机采用程控液晶屏按键设计，调整和设定简单、直观、方便；
- ※ 对蒸发箱清洗、杀菌、净化为一体；
- ※ 可以向风道内喷杀菌、净化和除味剂；也可以清洗空调冷凝器；
- ※ 去污剂和杀菌剂两个储液罐独立控制。可根据各种不同保养方式组合需要加入相应的液体；
- ※ 汽车蒸发箱等部位可视化内窥镜实时高清查看；
- ※ LED照明辅助；
- ※ 清洗管采用可调变形的蛇形管，操作灵活；
- ※ 汽车室内利用气雾和臭氧双重清洁消毒快速杀菌消除异味；
- ※ 臭氧杀菌去味；超微气雾负离子中和有害气体去味醒脑；

技术参数

输入电源电压：220V / 3A/150W
输入气源压力：8 kg/cm²
输出气源压力：0-5kg/cm²
雾化管：φ40x2m
7寸高分辨率TFT液晶屏
内窥镜线长：2.0m
压力表：0-10kg/cm²
液体输出管：2.3m
去污剂/杀菌剂贮液瓶：600ML
重量：50kg
包装尺寸：69X59X114cm

Features

- ※ Automobile air conditioning evaporator cleaning machine is designed with programmable LCD screen, simple to set and easy to use.
- ※ Combined the multiple functions of cleaning, sterilization and purification of the evaporator in one.
- ※ Sterilization, purification and deodorization of the air duct, and washing air conditioning condenser as well.
- ※ Both liquid tanks of detergent and sterilitant can be controlled independently. The corresponding liquid can be added as needed.
- ※ Evaporator and other parts can be viewed clearly at the visual endoscope.
- ※ Additional LED lighting
- ※ Cleaning hose is flexible and adjustable serpentine tube, easy to operate.
- ※ Use air mist spray and ozone to sterilize the air and eliminate odor in car's interior.
- ※ Ozone sterilizes air and ultra micro negative ion neutralizes harmful gas.

28家汽车制造商指定使用设备

出口 50 多个国家与地区

品质全球信赖



Specifications

Input power:220V / 3A/150W
Input air pressure:8 kg/cm²
Output air pressure:0-5kg/cm²
Spray hose: φ40x2m
TFT 7 inches LCD display
Endoscope cable length:2m
Pressure gauge:0~10kg/cm²
Output liquid hose:2.3m
Detergent/ Sterilitant tank:600ML
Weight:50kg
Size:69X59X114cm



空调系统多功能清洗机

Multifunction A/C Flush Machine

ACS-9800E

功能特点

- ※ ARM CORTEX-A9 4核 1.6GHz、1GB运行内存、8GB存储空间、工业显示屏 1024x600dpi、400流明高亮度、安卓智能系统，多媒体处理、用户交互界面、高分辨率广角显示、触摸滑动转换；
- ※ 除显示功能之外自带WIFI、蓝牙、千兆以太网、USB、影音播放、串口便于数据采集传输；
- ※ 除本地升级之外，通过网络方式在线更新迭代应用程序；
- ※ 可链接内窥镜，打印机设备；
- ※ 对每次保养内容进行网络保存及通过车架号查询保养记录；
- ※ 产品具有网络保存和查询功能，可对每次保养内容进行网络保存及通过车架号查询保养记录；
- ※ 对蒸发器清洗、杀菌、净化为一体；
- ※ 可以向风道内喷杀菌、净化和除味剂、也可以清洗空调冷凝器；
- ※ 去污剂和杀菌剂两个储液罐独立控制，可根据各种不同保养方式组合需要加入相应的液体；
- ※ 汽车蒸发器箱等部位可视化内窥镜时高清查看，LED照明辅助；
- ※ 清洗管采用可调变形的蛇形管，操作灵活；
- ※ 汽车室内利用气雾和臭氧双重清洁消毒快速杀菌消除异味；
- ※ 臭氧杀菌去味，超微气雾负离子中和有害气体去味醒脑；
- ※

Features

- ※ ARM cortex-A9 4 core 1.6GHz, 1GB running memory, 8GB storage space, industrial display 1024x600dpi with 400 lumen high brightness. Android intelligent operating system, multimedia processing, gorgeous user interfaces, high resolution with wide angle display effect, touch and scroll switching.
- ※ Abundant hardware interfaces. In addition to the functional display, it has WIFI, bluetooth, Ethernet, USB, serial port to facilitate data acquisition and transmission
- ※ In addition to local upgrades, it can also update iterate applications online through internet, making maintenance more easier.
- ※ Large hardware expansion capacity that can link to endoscopes, printers, and more.
- ※ Saving the maintenance data on the network and inquiring the maintenance records through the car frame number
- ※ With the functions of network storage and inquiry, saving the maintenance data on the network and inquiring the maintenance records through the car frame number
- ※ Combined the multiple functions of cleaning, sterilization and purification of the evaporator in one.
- ※ Sterilization, purification and deodorization of the air duct ,and washing air conditioning condenser as well.
- ※ Both liquid tanks of detergent and sterilant can be controlled independently. The corresponding liquid can be added as needed.
- ※ Evaporator and other parts can be viewed clearly at the visual endoscope. Additional LED lighting
- ※ Cleaning hose is flexible and adjustable serpentine tube, easy to operate.
- ※ Use air mist spray and ozone to sterilize the air and eliminate odor in car's interior.
- ※ Ozone sterilizes air and ultra micro negative ion neutralizes harmful gas.

技术参数

输入电源电压:220V / 3A/150W
 输入气源压力:8 kg/cm²
 输出气源压力:0-5kg/cm²
 雾化管:φ 40x2m
 内窥镜线长:2.5m
 压力表:0~10kg
 液体输出管:2.5m
 去污剂/杀菌剂贮液瓶:600ML
 重量:50kg
 包装尺寸:69X59X113cm

Specifications

Input power:220V / 3A/150W
 Input air pressure:8 kg/cm²
 Output air pressure:0-5kg/cm²
 Spray hose:φ 40x2m
 Endoscope cable length:2.5m
 Pressure gauge:0~10kg
 Output liquid hose:2.5m
 Detergent/ Sterilant tank:600ML
 Weight:50kg
 Size:69X59X113cm

29家汽车制造商指定使用设备

出口 50 多个国家与地区

品质全球信赖



侧视侧喷

内窥镜镜头侧视，正面观测更清晰、全面。
 喷头侧置，清洗液喷射更深入、有力、全面。

Side looking / Side spraying

The head of the endoscope allows users to have a side look and the front view is more clear and comprehensive.
 The spray head is placed on the side. Spray cleaning fluid more thorough, powerful and comprehensive.



清洗一体内窥镜

手持便携式设计，操作携带方便，直径9.0mm镜头、金属定型软管、耐折弯、易固定可拆卸、3.5寸高清显示屏带拍照录像、存储功能、带无线传输功能、微型高清摄像头、高亮度可调节LED灯。

Cleaning and Flushing Endoscope

Easy to carry and operation with hand-held design. With the diameter of 9.0 mm lens and bending resistance metal hose, it is easy to fixed and disassemble. The 3.5 inches display screen with wireless transmission miniature high-definition camera has storage function and adjustable high brightness LED light.

汽车冷却系统清洗换液机

Radiator Cooling System Flush Machine

WCS-6800

功能特点

- ※ 具有清洗、加注、回收、抽取冷却液功能;
- ※ 加注新液、回收旧液同步等量进行;
- ※ 出回液状态视窗观察;

技术参数

最大功率: DC12V-150W
工作压力: 0~2kg/cm²
出油管: 1.8m
回油管: 1.8m
新油桶: 20L
旧油桶: 20L
重量: 30kg
包装尺寸: 61 x 53 x 100 cm

Features

- ※ Fully functional- cleaning, refueling, collecting and extracting cooling liquid
- ※ Refueling new liquid and collecting old liquid at the same time and same quantity.
- ※ Fluid out and in is visible through the window

Specifications

Max Power: DC12V-150w
Working pressure: 0~2kg/cm²
Outlet hose: 1.8m
Inlet hose: 1.8m
New oil tank: 20L
Used oil tank: 20L
Weight: 30kg
Size: 61 x 53 x 100 cm

28家汽车制造商指定使用设备

出口 50 多个国家与地区

品质全球信赖



随机配套接头

汽车冷却系统清洗换液机

Radiator Cooling System Flush Machine

WCS-9800

功能特点

- ※液晶触摸屏，彩色图形功能菜单显示
- ※出回液状态大视窗实时显示
- ※具有清洗、加注、回收、抽取冷却液功能
- ※加注新液、回收旧液同步等量进行
- ※新液桶：20L
- ※旧液桶：20L

技术参数

- 最大功率：DC12V-250W
- 工作压力：0-2kg/cm²
- 出油管：2.3m
- 回油管：2.3m
- 重量：68 Kg
- 包装尺寸：69×59×103cm

Features

- ※Fully automatic operation, LCD touch screen display, color observation window design.
- ※Function with Cycle cleaning; Filling; Recovery of used oil; Extraction coolant;
- ※Shortage fluid alert
- ※Intelligent electronic control the full automatic equivalent exchange of new and used fluid.

Specifications

- Power supply: DC12V-250w
- Pressure gauge: 0-2kg/cm²
- Fluid outlet hose: 2.3 m
- Fluid return hose: 2.3 m
- New/used fluid tank: 20L×2
- Weight: 68Kg
- Size: 69×59×103cm

28家汽车制造商指定使用设备

出口 50 多个国家与地区

品质全球信赖



随机配套接头



发动机润滑系统免拆清洗机

Lubrication System Flush Machine

LCS-9800

功能特点

- ※ 彩色液晶触摸屏，智能图形功能菜单显示
- ※ 出回液状态大视窗观察
- ※ 透明过滤杯清晰观察5微米过滤效果
- ※ 任意设定加注量和清洗时间
- ※ 动态循环过滤清洗发动机润滑油道。
- ※ 加压气体冲刷功能彻底排出残留清洗油

技术参数

最大功率：220V-250W
工作压力：0~4kg/cm²
出油管：2.5m
回油管：2.5m
重量：74 Kg
包装尺寸：69×59×103cm

Features

- ※ Fully automatic operation. LCD touch screen display. color observation window design.
- ※ New/used oil color observation window design.
- ※ Randomly set new oil volume and cleaning time.
- ※ Dynamic circulating and cleaning engine lubrication system.
- ※ Pressurized purging thoroughly remove residue.

Specifications

Power supply: 220V-250w
Pressure gauge: 0~4kg/cm²
Fluid outlet hose: 2.5 m
Fluid return hose: 2.5 m
Filter precision: 5μm
Weight: 74Kg
Size: 69×59×103cm

28家汽车制造商指定使用设备

出口 50 多个国家与地区

品质全球信赖



随机配套接头(静态)



随机配套接头(动态)

